

Paslode Gas Systems

Paslode IM360Ci Li-ion Gas Framing Nailer



Paslode IM360Ci Li-ion cordless framing nailer offers best in class tool power, RounDrive® nails and NailScrew®, a long life Li-ion+ battery and outstanding cold weather performance, making it the only solution for the construction professional.

Applications

- Timber frame
- Truss work
- Stud work
- Roof battening
- External cladding
- Joists
- Floor boarding
- Noggins
- Soffits
- Roof decking
- Roofing
- Fencing
- Shuttering
- Decking
- Overboarding
- Hoarding

Features and Benefits

- Premium gas technology Li-ion nailer with intelligent power saving technology, increasing battery life up to 25%
- Incredible cold weather performance allows users to work down to -15°C
- Quick charge Li-ion+ battery: 13,000 shots per single charge, 200 in just 2 minutes
- One touch LED indicator shows remaining power and fuel
- IM360Ci fires both standard Paslode nails and innovative removable NailScrew®
- Improved aggressive probe / Easy to use depth adjuster
- On/off battery with lock position secures the battery and tool when not in use
- Market leading power to weight ratio

Innovative sensor




LED indicator



Long life battery



All weather



Code & Description

Code	Description	Qty
O10391	IM360Ci Li-ion Framing Nailer	1

Technical Specifications

Product weight with battery:	3.8 kg
Dimensions:	384 x 328 x 127mm
Impact force max:	105 J
Nail range:	50 - 90 mm
Max cycle rate per sec (fixings):	2-3
Max cycle rate per hour (fixings):	1,000
Magazine capacity:	47 nails
Long magazine capacity:	85 nails
Fuel cell capacity:	1,250 shots (-5°C)
Fixings per battery charge:	13,000
Battery charge time:	90 mins
Battery type:	Li-ion+
Noise Emission (EN 12549)	
Sound Power Level LwA 1s 1m:	109 dB(A)
Sound Pressure Level LpCpeak:	138 dB(A)
Vibration (EN ISO 8662-11) HAV:	3.9 m/s ²

Kit Contains

- IM360Ci framing nailer
- High impact carry case
- Li-ion+ battery 2.1Ah
- Li-ion battery charger
- Safety glasses to EN166:F
- Impulse lubricant
- Cleaning solution
- Allen key
- Instruction manual
- Safety instructions
- CE Declaration of Conformity



Paslode IM360Ci Nail Fuel Packs



RoundDrive® Nails (Premium Fixing) - A unique FULL HEAD design for 34° paper strip collation which offers optimum performance and the best quality finish available.



STAINLESS STEEL NAILS

Outdoor, exposed to weather. Service Class 3.

Code	Ø (mm)	Length (mm)	Shank	ST/ST	Fuel Cells	Box Qty
142045	2.8	51	Ring	A2	1	1,250
142047	2.8	63	Ring	A2	1	1,250
142055	2.8	63	Ring	A4	1	1,250
142050	3.1	80	Ring	A2	1	1,250



HOT DIPPED GALVANISED NAILS, min 55µm

Outdoor, exposed to weather. Service Class 3.

Code	Ø (mm)	Length (mm)	Shank	Fuel Cells	Box Qty
142014	2.8	63	Ring	3	3,750
142025	3.1	63	Ring	2	2,500
142031	3.1	75	Ring	2	2,500
142039	3.1	90	Smooth	2	2,500
142040	3.1	90	Ring	2	2,500



GALV-PLUS® NAILS, min 12µm

Indoor not heated, outdoor protected. Service Class 2.

Code	Ø (mm)	Length (mm)	Shank	Fuel Cells	Box Qty
142007	2.8	51	Ring	3	3,750
142062	2.8	51	Ring	1	1,250
142013	2.8	63	Ring	3	3,750
142063	2.8	63	Ring	1	1,250
142024	3.1	63	Ring	2	2,500
142030	3.1	75	Ring	2	2,500
142037	3.1	90	Smooth	2	2,500
142065	3.1	90	Smooth	1	1,250
142038	3.1	90	Ring	2	2,500



BRIGHT NAILS, min 5µm

Indoor. Service Class 1.

Code	Ø (mm)	Length (mm)	Shank	Fuel Cells	Box Qty
142005	2.8	51	Ring	3	3,750
142011	2.8	63	Ring	3	3,750
142029	3.1	75	Ring	2	2,500
142035	3.1	90	Smooth	2	2,500
142036	3.1	90	Ring	2	2,500

Paslode NailScrew® Nailscrew Fuel Packs



NailScrew® Fasteners - Six times faster than standard wood screws, offering improved fixing performance versus ring shank nails, with the ability to remove and rescrew. Ideal for cladding and temporary fixings.



STAINLESS STEEL A2-304 NAILScrew

Outdoor, exposed to weather. Service Class 3.

Code	Ø (mm)	Length (mm)	Shank	Drive	Fuel Cells	Box Qty
142101	2.8	50	Screw	TX15	1	1,250
142103	2.8	65	Screw	TX15	1	1,250
142105	2.8	75	Screw	TX15	1	1,250

FREE TORX BIT IN EVERY BOX.



ELECTRO GALVANISED NAILScrew, min 12µm

Indoor not heated, outdoor protected. Service Class 2.

Code	Ø (mm)	Length (mm)	Shank	Drive	Fuel Cells	Box Qty
142100	2.8	50	Screw	TX15	1	1,250
142102	2.8	65	Screw	TX15	1	1,250
142104	2.8	75	Screw	TX15	1	1,250

FREE TORX BIT IN EVERY BOX.

Accessories

Code	Description	Qty
300348	SERIES-i Fuel Cell Blister Pack	1
018880	Li-ion+ Battery 2.1Ah	1
018882	Li-ion Battery Charger	1
018889	Standard Magazine	1
013225	Long Magazine	1
013211	No-Mar Cladding Probe	1
013256	No-Mar Cladding Probe Rubber Tip	1
210610	No Mar Tip	1
013221	Tongue & Groove Probe	1
013223	Steel Tile Probe	1
014974	Ci Tool Carry Case	1
900507	In-car Charger Adaptor	1
013690	Impulse/Pulsa Cleaning Kit	1
115251	Impulse Cleaner 300ml	1
401482	Impulse Lubricating Oil	1
014121	Safety Glasses to EN166:F	1



018880



300348



013690



013211